## Flat suction cup (oval)

SAOF 60x23 NBR-60 RA

Part no..:10.01.05.00373

https://www.schmalz.com/10.01.05.00373



Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Suction Cups for Handling Sheet Metal > Flat Suction Cups SAOF (Oval) > SAOF 60x23 NBR-60 RA

### Flat suction cup (oval) for very dynamic handling of smooth and oily workpieces



Dimensions (LxB): 60x23


Suction cup material: Nitrile rubber NBR

Material hardness [Shore A]: 60 Shore A

Nipple material: Aluminum

Connection: RA

### **Design Data**



Attribute	Value
Bmax(S)	25 mm
Bs	21.60 mm
dn	4 mm
Н	21 mm
L4	32 mm
Lmax(S)	64 mm
Ls	60.60 mm
Z (Stroke)	3 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

#### **Technical Data**

Attribute	Value
Suction force (-600mbar)	57 N
Lateral force	37 N
Lateral force (oily surface)	33 N
Volume	3.89 cm <sup>3</sup>
Curve radius (min) (convex)	20 mm
Hose diameter (rec.) d	4 mm
Number of folds	0

# Flat suction cup (oval)

SAOF 60x23 NBR-60 RA

Part no..:10.01.05.00373

https://www.schmalz.com/10.01.05.00373



Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	60 Shore A
Weight	31 g
Product family	SAOF
Dimensions (LxB)	60x23

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m