Bellows suction cup (round)

SAB 125 NBR-60 G1/4-AG

Part no..:10.01.06.00825

https://www.schmalz.com/10.01.06.00825



Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Round) > Bellows Suction Cups SAB (1.5 Folds) > SAB 125 NBR-60 G1/4-AG


Number of folds: 1.5

Bellows suction cup (round) for very dynamic handling of smooth and oily workpieces



Size: 125
Suction cup material: Nitrile rubber NBR
Material hardness [Shore A]: 60 Shore A
Nipple material: Aluminum
Connection: G1/4-AG

Design Data



Attribute	Value
dn	6 mm
D1	94 mm
Dmax(S)	135 mm
Ds	126 mm
G1	G1/4"-M
Н	67.80 mm
LG1	10 mm
SW1	22 mm
Z (Stroke)	32 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

Technical Data

Attribute	Value
Suction force (-600mbar)	250 N
Pull-off force	558 N
Lateral force	410 N
Lateral force (oily surface)	335 N
Volume	220 cm ³
Curve radius (min) (convex)	140 mm
Hose diameter (rec.) d	9 mm

Contact Schmalz

Bellows suction cup (round)

SAB 125 NBR-60 G1/4-AG

Part no..:10.01.06.00825

https://www.schmalz.com/10.01.06.00825



Size	125
Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	60 Shore A
Weight	179.30 g
Product family	SAB
Number of folds	1.50

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m