# **Bellows suction cup (round)**



SAB 22 NBR-60 G3/8-IG

Part no..:10.01.06.01650

https://www.schmalz.com/10.01.06.01650


Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Round) > Bellows Suction Cups SAB (1.5 Folds) > SAB 22 NBR-60 G3/8-IG

### Bellows suction cup (round) for very dynamic handling of smooth and oily workpieces



Size: 22		
Suction cup material: Nitrile rubber NBR		
Material hardness [Shore A]: 60 Shore A		
Nipple material: Nickel plated		
Connection: G3/8-IG		
Number of folds: 1.5		

## **Design Data**



Attribute	Value
dn	3.50 mm
D1	22 mm
Dmax(S)	24 mm
Ds	20.60 mm
G1	G3/8"-F
Н	41 mm
LG1	9.50 mm
SW1	22 mm
Z (Stroke)	5.80 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

### **Technical Data**

Attribute	Value
Suction force (-600mbar)	16 N
Pull-off force	24 N
Lateral force	18 N
Lateral force (oily surface)	6 N
Volume	2.48 cm <sup>3</sup>
Curve radius (min) (convex)	20 mm
Hose diameter (rec.) d	4 mm

#### **Contact Schmalz**

Schmalz UK Limited | Unit 2 Woodrow Business Centre, Woodrow Way, Irlam, Manchester M44 6NN, Great Britain | +44 161 243 4642 | Page 1 from 2 schmalz@schmalz.co.uk

# **Bellows suction cup (round)**



SAB 22 NBR-60 G3/8-IG

Part no..:10.01.06.01650

https://www.schmalz.com/10.01.06.01650

Size	22
Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	60 Shore A
Weight	9 g
Product family	SAB
Number of folds	1.50

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m