Bellows suction cup (round)

SAB 60 NBR-60 G1/4-IG

Part no..:10.01.06.00852

https://www.schmalz.com/10.01.06.00852



Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Round) > Bellows Suction Cups SAB (1.5 Folds) > SAB 60 NBR-60 G1/4-IG


Bellows suction cup (round) for very dynamic handling of smooth and oily workpieces



Size: 60
Suction cup material: Nitrile rubber NBR
Material hardness [Shore A]: 60 Shore A
Nipple material: Nickel plated
Connection: G1/4-IG

Number of folds: 1.5

Design Data



Attribute	Value
dn	6 mm
D1	48 mm
Dmax(S)	67 mm
Ds	61.10 mm
G1	G1/4"-F
Н	46.30 mm
LG1	20 mm
SW1	22 mm
Z (Stroke)	14.50 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

Technical Data

Attribute	Value
Suction force (-600mbar)	82 N
Pull-off force	130 N
Lateral force	145 N
Lateral force (oily surface)	77 N
Volume	28.80 cm ³
Curve radius (min) (convex)	65 mm
Hose diameter (rec.) d	6 mm

Bellows suction cup (round)



Part no..:10.01.06.00852

https://www.schmalz.com/10.01.06.00852



Size	60
Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	60 Shore A
Weight	52.90 g
Product family	SAB
Number of folds	1.50

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m