## Flat suction cup (round)

SAF 60 NBR-45 G1/4-IG

Part no..:10.01.01.11451

https://www.schmalz.com/10.01.01.11451




Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Suction Cups for Handling Sheet Metal > Flat Suction Cups SAF > SAF 60 NBR-45 G1/4-IG

## Flat suction cup (round) for very dynamic handling of smooth and oily workpieces



Size: 60
Suction cup material: Nitrile rubber NBR
Material hardness [Shore A]: 45 Shore A
Nipple material: Nickel plated
Connection: G1/4-IG

## **Design Data**



Attribute	Value
dn	6 mm
Dmax(S)	67 mm
Ds	60.60 mm
G1	G1/4"-F
Н	36 mm
LG1	15 mm
SW1	22 mm
Z (Stroke)	6 mm

Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

### **Technical Data**

Attribute	Value
Suction force (-600mbar)	150 N
Lateral force	105 N
Lateral force (oily surface)	85 N
Volume	16.70 cm <sup>3</sup>
Curve radius (min) (convex)	75 mm
Hose diameter (rec.) d	6 mm
Size	60

# Flat suction cup (round)

SAF 60 NBR-45 G1/4-IG

Part no..:10.01.01.11451

https://www.schmalz.com/10.01.01.11451



Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	45 Shore A
Weight	37.10 g
Number of folds	0
Product family	SAF

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Lateral force: The specified lateral forces are values measured at a vacuum of -0.6 bar with a dry or oily, smooth, flat workpiece surface. Depending on the workpiece surface and its quality, the actual values may deviate from these values Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

### **Accessories**



### SU 60

Part no..:10.01.01.13585

### Size: 60

Clamping range: 60.0 ... 70.0 mm

Temperature resistance: 80 °C