Bellows suction cups (round)



FSG 4 NBR-55 M5-IG

Part no..:10.01.06.02965

https://www.schmalz.com/10.01.06.02965

Home > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Round) > Bellows Suction Cups FSG (2.5 Folds) > FSG 4 NBR-55 M5-IG

Bellows suction cup (round) for very uneven workpieces



Size: 4		
Suction cup material: Nitrile rubber NBR		
Material hardness [Shore A]: 55 Shore A		
Nipple material: Aluminum		
Connection: M5-F		
Number of folds: 2.5		
Vacuum connection: M5-F		

Design Data



Note: Acceptable dimensional tolerances for elastomer parts concerning to DIN ISO 3302-1 M3

Technical Data

Attribute	Value
Suction cup material	Nitrile rubber NBR
Material hardness [Shore A]	55 Shore A
Size	4
Number of folds	2.50
Connection	M5-IG
Curve radius (min) (convex)	4 mm
Volume	0.05 cm ³

Bellows suction cups (round)



FSG 4 NBR-55 M5-IG

Part no..:10.01.06.02965

https://www.schmalz.com/10.01.06.02965

Suction force (-600mbar)	0.27 N
Pull-off force	0.60 N
Hose diameter (rec.) d	2 mm
Weight	1.80 g
Product family	FSG

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a dry, smooth and flat workpiece surface - they do not include a safety factor Pull-off force: The pull-off force of the versions made of natural rubber is reduced by about 40% Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

Spare parts



SA-NIP N017 M5-IG DN200 Part no..:10.01.06.00313

art no...10.01.06.0031

Thread G1: M5-F

Fitting length: 10 mm

Material: Aluminum



FG 4 NBR-55 N017 Part no..:10.01.06.02962

Size: 4

Suction cup material: Nitrile rubber NBR Material hardness [Shore A]: 55 Shore A

Number of folds: 2.5